



DESIGN PARAMETERS	
ROAD LEVEL	1 (iii)
ROADWORKS TYPE	B
SPEED LEVEL	50Km/h
TEMPORARY SIGNS	
SIGN VISIBILITY	25m
NUMBER OF SIGNS	2
SIGN SPACING	20m
SIGN SIZE	600MM
RATE OF TAPER	
ENTRY TAPER	20M
SAFETY ZONE	
LONGITUDINAL	5.0m
LATERAL	0.5m
MINIMUM CONE SPACING	
AT TAPERS	1.0m
LONGITUDINAL	2.5m
MINIMUM LANE WIDTH	
	3.0m
TRAFFIC MANAGEMENT SYSTEM	
METHOD	"Two Way"
1. WORKS TO BE CARRIED OUT IN ACCORDANCE WITH ALL RELEVANT AUTHORITIES & CONTRACT REQUIREMENTS 2. SEQUENCE OF WORKS TO BE AGREED ONSITE 3. MINIMUM SINGLE LANE TRAFFIC LANE WIDTH 3m (MAXIMUM 3.7m) TO BE MAINTAINED AT ALL TIMES USE 3.25m IF POSSIBLE 4. ALL SIGNS TO BE RETROREFLECTIVE 5. EXACT SIGN POSITIONS TO BE AGREED ON SITE 6. SIGN SIZE TO BE 600mm 7. ALL TRAFFIC CONES SHALL CONFORM TO EN 134422:2004 AND HAVE REFLECTIVE SLEEVE 8. MINIMUM HEIGHT OF CONE TO BE 750mm 9. APPROPRIATE SAFETY ZONES, LATERAL AND LONGITUDINAL TO BE PROVIDED AND MAINTAINED AT ALL TIMES 10. TEMPORARY TRAFFIC SIGNALS, SIGNAGE, DELINEATORS TO BE IN ACCORDANCE WITH TRAFFIC SIGNS MANUAL (DEPARTMENT OF TRANSPORT TOURISM & SPORT AUGUST 2019)	
Pedestrian Route	

121 sábháilteacht
www.121safety.ie

121 SAFETY LTD
Simonstown, Coole,
Mullingar, Co. Westmeath
T: +353 (87) 2838220
121safety@gmail.com



Project Title:
Bank Of Ireland Drogheda

Drawing Title:
Traffic / Pedestrian Management Plan

Revision Details Box	
Rev. No.	Comments

Drawn:	Scale:	Drawing No.
AMCM	NTS	001
Approved:	Date:	Rev:
	06/23	